



# AGRIMOT ULTRATEC FE 5W-30



Very high performance lubricant, fully synthetic, dedicated to CLAAS agricultural machinery, providing fuel economy.

## Applications

### Loaded Diesel engines EURO Stage I, II or IIIa

Particularly suitable for the lubrication of the latest generation of Diesel engines developed by European manufacturers and more specifically FPT Cursor engines.

Specially dedicated to turbo-charged Diesel engines.

Can, nevertheless, be used in naturally aspirated engines.

Can handle the most severe applications.

## Performances



Classifications: ACEA E4, E7

Manufacturers approvals: DTFR 15B120 • LIEBHERR LH-00-ENG • MAN M 3277

Conforms to the specifications: FPT-Iveco TFE

## Customer benefits

### Security under loaded conditions

Recommended by all European engine manufacturers in case of severe working conditions.

Exceptional anti-wear and detergency properties.

### Technical performances

Exceptional performances due to the lubricant's synthetic base oil added to high performance additives.

### Economy

Easier start-up at low temperatures.

Provides Fuel economy thanks to the reduction of mechanical losses at start-up and at operating temperature.

## Characteristics\*

AGRIMOT ULTRATEC FE 5W-30	Units	Value
Kinematic viscosity at 40° C	mm <sup>2</sup> /s	72
Kinematic viscosity at 100° C	mm <sup>2</sup> /s	12.2
Viscosity index	-	168
T.B.N	mg KOH/g	16
Pour point	° C	-42

\* The typical characteristics mentioned represent mean values

AGRIMOT AGRITEC FE 5W-30 – Sheet updated 01/2021 – Developed with TOTAL technology at the service of CLAAS

This lubricant used in accordance with our recommendations and for the applications for which it is intended does not represent a special hazard.  
A safety data sheet conforming to the requirements of current E.U. legislation is available from your local trade consultant.

