



# AGRIMOT ULTRATEC 10W-40

Very high-performance lubricant for Diesel engines based upon a synthetic technology.

## Applications

### Loaded Diesel engines Phases I, II or IIIa

Particularly suitable for the lubrication of the latest generation of Diesel engines developed by European manufacturers.

New generation synthetic technology lubricant for all types of Diesel engines, turbo-charged or naturally aspirated, which are found on agricultural vehicles.

Can handle the most severe applications

## Performances



Classifications: ACEA E4, E7 • API CF

Manufacturers approvals:

DTFR 15B120

DEUTZ DQC III-10

MAN M 3277

Suitable for: FPT-Iveco T3 E4

## Customer benefits

### Safety in conditions of maximum load

Product recommended by all European manufacturers in case of severe conditions of use.

Facilitates cold starts.

Excellent anti-wear and detergent properties.

### Performances techniques

Excellent service stability.

Excellent dispersion, anti-corrosion and anti-oxidizing properties.

Exceptional performance due to the synthetic base of the lubricants and to high performance additives.

## Characteristics\*

AGRIMOT ULTRATEC 10W-40	Units	Value
Kinematic viscosity at 40° C	mm <sup>2</sup> /s	85
Kinematic viscosity at 100° C	mm <sup>2</sup> /s	13.1
Viscosity index	-	157
Pour point	° C	-42

\* The typical characteristics mentioned represent mean values

AGRIMOT ULTRATEC 10W-40 – Sheet updated 01/2021 – Developed with TOTAL technology at the service of CLAAS

This lubricant used in accordance with our recommendations and for the applications for which it is intended does not represent a special hazard.  
A safety data sheet conforming to the requirements of current E.U. legislation is available from your local trade consultant.

**CLAAS**