

Hi-Perf 4T 500 20W-50 (SL)

4-Stroke Engine Oil

KEY DATA



Premium mineral engine oil

INTERNATIONAL STANDARDS

- JASO MA2 - M033TOL363
- API SL

TECHNOLOGIES

Durability Improver technology

4 Actions to maximize the durability of your bike:

- Protection against harmful piston deposits
- Protection against gear pitting and wear
- Protection against clutch slippage
- Protection against thermo-oxidative attack



APPLICATIONS

Hi-Perf 4T 500 20W-50 is a premium 4-stroke engine oil for motorcycles. Formulated with Durability Improver technology, it is Specially designed to provide superior protection against oxidation and deposits, which results in enhanced cleanliness of your engine.

PERFORMANCES & CUSTOMER BENEFITS

- Maintains engine cleanliness: Helps reduce the formation of deposits and sludge, keeping the engine running smoothly over time.
- Supports smooth gear operation: Designed to ensure stable lubrication of the gearbox for consistent riding comfort.
- Reliable clutch performance: Optimized for wet clutch compatibility to provide smooth and controlled power transfer.
- Performs well in high temperatures: Offers excellent thermal resistance for consistent protection in hot or stop-and-go conditions.

CHARACTERISTICS*

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	20W-50
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	162.6
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	17.9
Flash Point	°C	ASTM D92	208
Viscosity index	-	ASTM D2270	121
Pour point	°C	ASTM D97	-30
Density	kg/m ³	ASTM D1298	881.9

*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

