



Prosylva 4T 15W-40

Engine oil

KEY DATA





Mineral oil designed for 4-stroke engines used in mechanized farming.

INTERNATIONAL STANDARDS

♦ API CF-4/SG

APPLICATIONS

Prosylva 4T 15W-40 is particularly adapted to **4 stroke gasoline or Diesel engines**, for **gardening** and **mechanized farming**.

Prosylva 4T 15W-40 can also be used for **gardening material when a monograde SAE 30 oil is recommended**.

PERFORMANCES & CUSTOMERS BENEFITS

- Prosylva 4T 15W-40 has outstanding thermal stability, ensuring efficient lubrication of hot engine parts.
- Its exceptional oil film resistance when hot guarantees good engines operation and no performance losses.
- Prosylva 4T 15W-40 contains excellent viscosity stability in service, providing smooth cold starts.
- ♦ The association of detergent, dispersant and anti-wear additives keeps the engine clean and enables effective control of soot, sludge and piston deposits.
- Its anti-rust and anti-corrosion properties protect the engine from moisture damages.

CHARACTERISTICS*

TEST	UNIT	TEST METHOD	RESULT
Density at 15°C	kg/m³	ASTM D1298	887
Kinematic viscosity at 40°C	mm²/s	ASTM D445	101
Kinematic viscosity at 100°C	mm²/s	ASTM D445	14
Viscosity index	-	ASTM D2270	141
Pour point	°C	ASTM D97	-33
T.B.N	mgKOH/g	ASTM D2896	8.5

^{*}The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at https://ms-sds.totalenergies.com.

This product should not be used for any purposes other than the ones for which it is intended.



TotalEnergies Lubrifiants / Last update of this datasheet: July 24 / Prosylva 4T 15W-40

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at www.lubricants.totalenergies.com.