

ELF RENAULTMATIC D2 is a Automatic Transmission and Power Steering Fluid.

Technical Data Sheet

Manufacturers
Approvals

Meets the requirement of :
GM DEXRON® II-D

* Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

1 - Applications

ELF RENAULTMATIC D2 is a special fluid for automatic and hydrostatic transmission systems, recommended for all RENAULT cars and vans.

Do not use ELF RENAULTMATIC D2 in automatic transmission and powerassisted steering systems of other brands of vehicle.

2 - Customer Benefits

- Fluid and viscous properties adjusted for the coefficients of friction required for satisfactory clutch operation.
- High viscosity number.
- Very low pour point.
- Advanced protection against wear, corrosion and foaming.
- Excellent thermal and chemical stability.
- Smooth compatibility with seals.
- Ensures precision and flexibility of automatic sequences, even at very low speeds and in any weather.

3 - Characteristics

TEST	TEST METHOD	UNITS	VALUE
Density at 15°C	ASTM D1298	kg/m ³	867
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s	33.73
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	7.296
Viscosity index	ASTM D2270	-	190
Pour point	ASTM D97	°C	-51
Flash point	ASTM D92	°C	208
TBN	ASTM D2896	mgKOH/g	-
Sulphated Ash	ASTM D874	% m/m	-

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

4 - Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements.

Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

5 - Health, Safety and The Environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

The SDS is available on request from your local reseller and at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.