



AGRIGREASE EP 2

Multi-purpose extreme pressure lithium/calcium grease.

Applications

Multi purpose EP grease
General Lubrication

Multi-purpose extreme pressure grease, formulated for the lubrication of all agricultural applications, operating in dusty, wet or dry conditions.

Also suitable as EP multi purpose grease, in "off road" applications where water and/or dust are in frequent contact with the grease.

Always avoid contamination of the grease.

Preferably use a pneumatic pump system or cartridges

Performances



Specification: **EP 2 Grease • NLGI 2**

Meets the requirements of the following standards:

ISO 6743-9 : L-XBCEB 2

DIN 51502 : KP2K-25

Customer benefits

Multi-purpose

Because of its true Multi-Purpose character, it may replace a wide range of greases, allowing stock rationalization and simplified maintenance.

Miscibility

Forms a durable lubrication film, resulting in reduction of maintenance and down-time costs.

Miscible with most other conventional soap greases.

No harmful substances

Excellent mechanical stability avoiding ejection or loss of consistency.

Excellent adhesion to metal.

Good thermal stability, leading to high resistance to temperature variations.

Does not contain lead, or any other heavy metals considered harmful to human health and the environment.

Characteristics*

AGRIGREASE EP 2	Units	Value
NLGI grade	-	2
Soap / thickener	-	Lithium / Calcium
Colour	-	Sepia brown
Appearance	-	Smooth
Operating temperature range	° C	-25 to 130
Dropping point	° C	> 190
Four ball weld load	daN	260 / 280

* The typical characteristics mentioned represent mean values

AGRIGREASE EP 2 - Sheet updated 07/2017 – Developed with TOTAL technology at the service of CLAAS

This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard.
A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.

CLAAS

