



TOTAL QUARTZ 7000 DIESEL 10W-40

Engine oil

KEY DATA

LIGHT VEHICLE RANGE



*
5000



**
7000



9000



INEO

DIESEL ENGINE OIL

SAE 10W-40

SYNTHETIC BASED TECHNOLOGY

INTERNATIONAL STANDARDS

- ✓ ACEA A3/B4
- ✓ API SL/CF

MANUFACTURER APPROVALS

- ✓ PSA PEUGEOT CITROËN B71 2294 & B71 2300
- ✓ VOLKSWAGEN 501.01/505.00
- ✓ MERCEDES-BENZ MB-Approval 229.1

APPLICATIONS

TOTAL QUARTZ 7000 DIESEL 10W-40 is a synthetic based technology engine oil that has been developed to cover the most stringent requirements of (passenger cars and light vans) diesel engines*.

TOTAL QUARTZ 7000 DIESEL 10W-40 is specifically developed to answer the requirements of recent Diesel engines, namely the direct injection with or without common rail.

TOTAL QUARTZ 7000 DIESEL 10W-40 is perfectly suited to all driving conditions and styles.

* The vehicle owner manual should be checked before using.

CUSTOMER BENEFITS

- **Manufacturers Standards:** TOTAL QUARTZ 7000 DIESEL 10W-40 satisfies rigorous manufacturer standards (see above), while guaranteeing perfect and constant quality.
- **Resistance to Oxidation:** Thanks to the good quality of its base oils and additives, TOTAL QUARTZ 7000 DIESEL 10W-40 provides a specific resistance to oxidation.
- **Engine protection and cleanliness:** Excellent detergent properties giving greater engine cleanliness for optimum performance.
- **Long-term wear Protection:** Long-term wear protection of engine parts (distribution, ring, plunger and liner) increasing engine life.

CHARACTERISTICS*

Test	Unit	Test method	Result
Viscosity grade	-	SAE J300	10W-40
Density at 15°C	kg/m ³	ASTM D1298	873
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	96.8
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	14.8
Viscosity index	-	ASTM D2270	160
Flashpoint	°C	ASTM D92	231.7
Pour point	°C	ASTM D97	-24

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at www.quickfds.fr.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.