

Quartz Ineo Pro 0W-30

Engine oil

KEY DATA



LIGHT VEHICLE RANGE

GASOLINE & DIESEL ENGINE OIL
SAE 0W-30
ADVANCED SYNTHETIC TECHNOLOGY
LOW SAPS

MANUFACTURER APPROVALS ¹

 STELLANTIS FPW9.55535-DH1

¹Please refer to car owner's manual

TECHNOLOGY

Age-Resistance technology

The next gen oil for outstanding protection.

Age-Resistance technology provides expert protection, to fight everyday challenges in the long term.

Age-Resistance technology offers unbeatable engine protection. It's unique combination of hyperactive molecules creates a strong thick oil film on all concerned engine parts. Engines are absolutely protected against a variety of challenges, from wear to oil oxidation even at extreme temperatures.



APPLICATIONS

The Quartz Ineo Pro 0W-30 is a high-tech advanced synthetic engine oil offering exceptional performance in maintaining turbocharger cleanliness and reduces wear. Thanks to a close collaboration between the technical teams at Stellantis and TotalEnergies Lubrifiants, the Quartz Ineo Pro 0W-30 is officially approved STELLANTIS FPW9.55535-DH1.

Quartz Ineo PRO 0W-30 is designed for 2.2L diesel engines used in all European Stellantis light commercial vehicles (LCVs) who required a high-performance lubricant approved for the stringent requirements of the STELLANTIS FPW9.55535-DH1 specification.

By choosing Quartz Ineo Pro 0W-30, you're not only selecting a high-performance lubricant but also investing in the future of your vehicle by extending engine life and contributes to better fuel economy.

CUSTOMERS BENEFITS

- Outstanding protection against wear: The outstanding technology of this product makes it an optimal choice in terms of robustness and provides a complete protection for the pistons, rings and liner.
- High resistance to LSPI (Low Speed Pre-Ignition): Specially formulated to prevent damage, CO2 and pollutant emissions caused by LSPI.
- Longer service life for particulate filter: Maximises the efficiency of particulate filters (DPF, GPF), preventing them from getting clogged up prematurely.
- Optimum protection against engine contamination: The detergent and specific dispersive additives provide the engine with optimum protection against wear and prevent the formation of soot and sludge deposits.

CHARACTERISTICS²

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	0W-30
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	53,3
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	9,64
Density at 15°C	kg/m ³	ASTM D1298	843
Viscosity index	-	ASTM D2270	167
Pour point	°C	ASTM D97	-51
OC Flash point	°C	ASTM D92	>210

²The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

